

[0296] Here, where controller 260 broadcasts a message asking all devices (e.g., pumps 100, monitor 830, and other treatment devices) to identify themselves, each device transfers a communication address that controller 260 can use to obtain pump status or the patient's physiologic measurements. Alternately, physician identification device 40 can be used to read a tag, similar to tag 131, affixed to monitor 830. The tag would include a wireless channel address used by controller 260 to address monitor 830 to receive the physiologic measurements for the patient. Indicator 834 can be activated under circumstances when it is desirable to visually identify that monitor 830 is addressed by controller 260, (e.g., when controller 260 is receiving information from monitor 830 or sending information to monitor 830). By visually identifying monitor 830 a physician can verify that the addressed monitor is in fact monitoring the patient associated with controller 260. In some instances indicator 834 can be replaced by a message or graphic image presented on a display 831.

[0296] Here, where controller 260 broadcasts a message asking all devices (e.g., pumps 100, monitor 830, and other treatment devices) to identify themselves, each device transfers a communication address that controller 260 can use to obtain pump status or the patient's physiologic measurements. Alternately, physician identification device 40 can be used to read a tag, similar to tag 131 ~~132~~, affixed to monitor 830. The tag would include a wireless channel address used by controller 260 to address monitor 830 to receive the physiologic measurements for the patient. Indicator 834 can be activated under circumstances when it is desirable to visually identify that monitor 830 is addressed by controller 260, (e.g., when controller 260 is receiving information from monitor 830 or sending information to monitor 830). By visually identifying monitor 830 a physician can verify that the addressed monitor is in fact monitoring the patient associated with controller 260. In some instances indicator 834 can be replaced by a message or graphic image presented on a display 831.